



In-use photo - circuit boards not included

	<u>8521</u>	Single Card Carrier, 9" x 12" x 1.25" (229mm x 305mm x 32mm)	
	<u>8522</u>	Single Card Carrier, 17" x 18" x 2" (432mm x 457mm x 51mm)	
İ	<u>8523</u>	Single Card Carrier, 10" x 8" x 2" (254mm x 203mm x 51mm)	

"It should be understood that any object, item, material or person could be a source of static electricity in the work environment. Removal of unnecessary nonconductors, replacing nonconductive materials with dissipative or conductive materials and grounding all conductors are the principle methods of controlling static electricity in the workplace, regardless of the activity." [ESD Handbook ESD TR20.20 section 2.4 Sources of Static Electricity]

Features

- Static Shielding Single Card Carrier with Dissipative Cushioning Foam. Ideal for static-safe storage and in-process handling and transporting. Protects individual printed circuit boards from static and physical damage during storage and transport
- Made from Velostat® injection molded, conductive polypropylene
- Includes a 10mm Female Snap Socket (can use a ground cord [not included] with a 10mm male stud snap to attach to ground)
- Carriers are noncorrosive and lightweight
- Meets ANSI/ESD S20.20 and Packaging Standard ANSI/ESD S4.1
- · Made in the United States of America

Specifications

Property - Plastic	Test Method	Value
Hardness	ASTM D2240	67-71 Shore D
Maximum Temp. Exposure		180°F
Tensile Strength	ASTM D638	2800 - 3000 psi
Flex Modulus	ASTM D790	130,00 - 150,000 psi
Electrical Conductance		
Volume Conductive	ASTM D991	<500 ohms/cm
Volume Resistance	ANSI/ESD STM11.12	<1 x 10 ⁴ ohms

Properties - Foam	Test Method	Value
Density	ASTM D3574-08	1.4 lb
Compression Set @ 50%	ASTM D3574-08	10%
Tensile Strength	ASTM D3574-08	12.0 psi
Surface Resistivity	ASTM D257	1 x 10 ¹¹ ohms square
Static Decay	FTMS 101C	2.0 seconds

Chemical Resistance	Reactions	
Alcohol	Resistant	
Aromatic Hydrocarbons	Severe Attack	
Aliphatic Hydrocarbons	Moderate Attack	
Concentrated Acids	Slight Attack	
Concentrated Alkalines	Slight Attack	
Kerosene	Severe Attack	
Ketones (Acetone)	Moderate Attack	
Mineral Oil	Slight Attack	
Oil & Gasoline	Moderate Attack	



Specifications and procedures subject to change without notice

Unless otherwise noted, tolerance is ±10%

PROTEKTIVE PAK

Velostat® Single Card Carriers

PROTEKTIVE PAK

13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578 ProtektivePak.com

DRAWING NUMBER 8521 **DATE:**November 2017